

Garant
Solid carbide T-slot cutter, semi-roughing, TiAlN, \varnothing DC \times LC d11 \times d11: 32X14 mm

Order data

Order number	208027 32X14
GTIN	4062406397296
Item class	11X

Description
Version:

With new high-performance coating for very long tool life. The sides of the teeth are ground to give clearance and thus cannot jam in the component. With semi-roughing profile.

Note:

For milling T-slots to DIN 650.

Feed at 50 % f_z until full engagement.

Type: NF

No. of teeth Z: 6

No. of teeth Z: 6

for T-slots DIN 650: 18 mm

Recess \varnothing D₁: 15 mm

Overall length L: 90 mm

Shank \varnothing D_s: 16 mm

Corner chamfer width at 45°: 0.2 mm

Technical description

Cutting edge \varnothing D _c	32 mm
Shank \varnothing D _s	16 mm
for T-slots DIN 650	18 mm
No. of teeth Z	6
Type	NF

Feed f_z in steel < 900 N/mm ²	0.035 mm
Corner chamfer width at 45°	0.2 mm
Recess $\varnothing D_1$	15 mm
Overall length L	90 mm
Flute length L_c	14 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 851
Milling profile	staggered teeth
Tolerance nominal \varnothing	d11
Helix angle	12 degrees
Direction of infeed	horizontal
Shank	DIN 6535 HB to h6
Through-coolant	no
Shank tolerance	h6
Corner chamfer angle	45 degrees
Colour ring	green
Type of product	End mill