

Garant
Solid carbide chamfer mill 60°, uncoated, Ø e8 DC: 3 mm

Order data

Order number	208065 3
GTIN	4045197854773
Item class	11X

Description
Version:

Tolerance: Point angle $\pm 1^\circ$.

Application:

- **Countersinking**
- **Chamfering**

Note:

For **HB** shanks use order **No. 208068**.

HB shanks are available at the same price as HA.

No. of teeth Z: 2

Shank: DIN 6535 HA with h6

Chamfer mill: 30 degrees

No. of teeth Z: 2

Flute length L_c : 8 mm

Overall length L: 57 mm

Shank $\varnothing D_s$: 6 mm

Feed f_z for side milling in steel < 900 N/mm²: 0.01 mm

Technical description

Flute length L_c	8 mm
Overall length L	57 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.01 mm
Shank $\varnothing D_s$	6 mm
No. of teeth Z	2

Cutting edge $\varnothing D_c$	3 mm
Shank	DIN 6535 HA with h6
Corner chamfer angle	60 degrees
Chamfer mill	30 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	e8
Helix angle	30 degrees
Cutting width a_e for milling operation	0.5×D for side milling
Countersink tip angle	60 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	without
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------