

Garant
Solid carbide chamfer mill 60°, uncoated, Ø e8 DC: 10 mm

Order data

Order number	208068 10
GTIN	4062406538194
Item class	11X

Description
Version:

Tolerance: Point angle $\pm 1^\circ$.

Application:

- **Countersinking**
- **Chamfering**

No. of teeth Z: 2

Shank: DIN 6535 HB to h6

Chamfer mill: 30 degrees

No. of teeth Z: 2

Flute length L_c : 22 mm

Overall length L: 72 mm

Shank $\varnothing D_s$: 10 mm

Feed f_z for side milling in steel $< 900 \text{ N/mm}^2$: 0.05 mm

Technical description

Chamfer mill	30 degrees
Shank	DIN 6535 HB to h6
No. of teeth Z	2
Cutting edge $\varnothing D_c$	10 mm
Overall length L	72 mm
Flute length L_c	22 mm
Corner chamfer angle	60 degrees

Shank $\varnothing D_s$	10 mm
Feed f_z for side milling in steel $< 900 \text{ N/mm}^2$	0.05 mm
Coating	uncoated
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Tolerance nominal \varnothing	e8
Helix angle	30 degrees
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Countersink tip angle	60 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	without
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------