

Garant
Solid carbide chamfering cutter 120°, uncoated, Ø e8 DC: 3 mm

Order data

Order number	208081 3
GTIN	4062406544928
Item class	11X

Description
Version:
Tolerance: Point angle $\pm 1^\circ$.

Application:

- **Slot milling**
- **Countersinking**
- **Milling**
- **Can also be used as a NC spotting drill.**

No. of teeth Z: 2

Shank: DIN 6535 HA to h6

Chamfer mill: 60 degrees

No. of teeth Z: 2

 Flute length L_c : 8 mm

Overall length L: 57 mm

 Shank $\varnothing D_s$: 6 mm

 Feed f_z for side milling in steel $< 900 \text{ N/mm}^2$: 0.01 mm

Technical description

No. of teeth Z	2
Shank	DIN 6535 HA to h6
Corner chamfer angle	30 degrees
Flute length L_c	8 mm
Chamfer mill	60 degrees
Cutting edge $\varnothing D_c$	3 mm

Feed f_z for side milling in steel < 900 N/mm ²	0.01 mm
Overall length L	57 mm
Shank $\varnothing D_s$	6 mm
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	e8
Helix angle	30 degrees
Cutting width a_e for milling operation	0.5×D for side milling
Countersink tip angle	120 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	without
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------