


Solid carbide deburrer 90°, TiAlN, Ø h6 DC: 8 mm

Order data

Order number	208107 8
GTIN	4045197858832
Item class	12X

Description
Version:

Tolerance: **Dimension S** = ± 0.1 mm, point angle ± 10 arc minutes.

Application:

Perfectly suitable for **chamfering** and **deburring** component edges and for **contouring applications**.

No. of teeth Z: 4

Shank: DIN 6535 HA with h6

Chamfer mill: 45 degrees

No. of teeth Z: 4

Dimension S: 5.6 mm

Overall length L: 59 mm

Shank Ø D_s: 8 mm

Feed f_z in steel < 900 N/mm²: 0.04 mm

Technical description

Overall length L	59 mm
Cutting edge Ø D _c	8 mm
No. of teeth Z	4
Shank	DIN 6535 HA with h6
Shank Ø D _s	8 mm
Feed f _z in steel < 900 N/mm ²	0.04 mm
Dimension S	5.6 mm

Corner chamfer angle	45 degrees
Chamfer mill	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal Ø	h6
Direction of infeed	horizontal and oblique
Countersink tip angle	90 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	without
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------