


**Solid carbide deburrer 90°, uncoated, Ø h6 DC: 8 mm**

**Order data**

Order number	208111 8
GTIN	4045197199720
Item class	12X

**Description**
**Version:**

Tolerance: **Dimension S = ±0.1 mm, point angle ±10 arc minutes.**

**Application:**

Perfectly suitable for **chamfering** and **deburring** component edges and for **contouring applications**.

No. of teeth Z: 4

Shank: DIN 6535 HB to h6

Chamfer mill: 45 degrees

No. of teeth Z: 4

Dimension S: 5.6 mm

Overall length L: 59 mm

Shank Ø D<sub>s</sub>: 8 mm

Feed f<sub>z</sub> in steel < 900 N/mm<sup>2</sup>: 0.04 mm

**Technical description**

Feed f <sub>z</sub> in steel < 900 N/mm <sup>2</sup>	0.04 mm
No. of teeth Z	4
Cutting edge Ø D <sub>c</sub>	8 mm
Dimension S	5.6 mm
Shank Ø D <sub>s</sub>	8 mm
Overall length L	59 mm
Shank	DIN 6535 HB to h6

Corner chamfer angle	45 degrees
Chamfer mill	45 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal $\varnothing$	h6
Direction of infeed	horizontal and oblique
Countersink tip angle	90 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	without
Type of product	End mill