

Garant
Solid carbide deburrer 60°, uncoated, Ø h6 DC: 16 mm

Order data

Order number	208140 16
GTIN	4045197457141
Item class	11X

Description
Version:

Tolerance: **Dimension S = ±0.1 mm, point angle ±10 arc minutes.**

With special flute geometry for smooth cutting.

Application:

Perfectly suitable for **chamfering** and **deburring** component edges and for **contouring applications**.

No. of teeth Z: 4

Shank: DIN 6535 HB to h6

Chamfer mill: 30 degrees

No. of teeth Z: 4

Dimension S: 15.8 mm

Overall length L: 93 mm

Shank Ø D_s: 16 mm

Feed f_z in steel < 900 N/mm²: 0.08 mm

Technical description

Dimension S	15.8 mm
Feed f _z in steel < 900 N/mm ²	0.08 mm
No. of teeth Z	4
Cutting edge Ø D _c	16 mm
Shank Ø D _s	16 mm
Overall length L	93 mm
Shank	DIN 6535 HB to h6

Corner chamfer angle	60 degrees
Chamfer mill	30 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	h6
Direction of infeed	horizontal and oblique
Countersink tip angle	60 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	without
Type of product	End mill