

Garant
Diabolo solid carbide deburrer, spiral flutes 90°, TiAlN, Ø h6 DC: 10M mm

Order data

Order number	208158 10M
GTIN	4062406378905
Item class	11X

Description
Version:

Tolerance: **Dimension S = ± 0.2 mm.**

Point angle = ±5 arc minutes.

Deburrer specially developed for **hard machining**. The further development of the Diabolo coating permits even longer tool life and improved surface quality.

Outstanding surface qualities thanks to the 35° **helix angle**. Extra-long deburrers for outstanding deburring results on particularly difficult-to-access contours.

Application:

Perfectly suitable for **chamfering** and **deburring** component edges and for **contouring applications**.

No. of teeth Z: 6

Shank: DIN 6535 HA to h6

Chamfer mill: 45 degrees

small Ø D₃: 5 mm

large Ø D₂: 10 mm

No. of teeth Z: 6

Dimension S: 3.5 mm

Overall length L: 100 mm

Shank Ø D_s: 10 mm

Technical description

Corner chamfer angle	45 degrees
Overall length L	100 mm
Chamfer mill	45 degrees

Series	Diabolo
large $\varnothing D_2$	10 mm
Cutting edge $\varnothing D_c$	10 mm
Dimension S	3.5 mm
Shank $\varnothing D_s$	10 mm
Shank	DIN 6535 HA to h6
No. of teeth Z	6
Feed f_z in steel < 60 HRC	0.035 mm
small $\varnothing D_3$	5 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Tolerance nominal \varnothing	h6
Helix angle	35 degrees
Direction of infeed	horizontal and oblique
Countersink tip angle	90 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	red
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------