

Garant

Solid carbide deburrer 60°, TiAlN, Ø h6 DC: 12 mm



Order data

Order number	208160 12
GTIN	4045197129413
Item class	11X

Description

Version:

Tolerance: **Dimension S = ±0.1 mm, point angle ±10 arc minutes.**

With special flute geometry for smooth cutting.

Application:

Perfectly suitable for **chamfering** and **deburring** component edges and for **contouring applications**.

No. of teeth Z: 4

Shank: DIN 6535 HB to h6

Chamfer mill: 30 degrees

No. of teeth Z: 4

Flute length L_c: 11.9 mm

Dimension S: 11.9 mm

Overall length L: 83 mm

Shank Ø D_s: 12 mm

Feed f_z in steel < 900 N/mm²: 0.06 mm

Technical description

Feed f _z in steel < 900 N/mm ²	0.06 mm
Dimension S	11.9 mm
Cutting edge Ø D _c	12 mm
No. of teeth Z	4
Shank Ø D _s	12 mm
Flute length L _c	11.9 mm

Overall length L	83 mm
Shank	DIN 6535 HB to h6
Corner chamfer angle	60 degrees
Chamfer mill	30 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal Ø	h6
Direction of infeed	horizontal and oblique
Countersink tip angle	60 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	without
Type of product	End mill