

**Garant**
**Solid carbide deburrer, spiral flutes 60°, TiAlN, Ø h6 DC: 8 mm**

**Order data**

Order number	208165 8
GTIN	4062406380342
Item class	11X

**Description**
**Version:**

**Outstanding surface qualities** thanks to the **35° helix angle**.

Deburrer for **universal application** on virtually all materials. The newly developed coating effectively prevents built-up edges, even in aluminium or stainless steel.

Tolerance: **Dimension S = ± 0.2 mm. Point angle ±5 arc minutes.**

**Application:**

Perfectly suitable for **chamfering** and **deburring** component edges and for **contouring applications**.

No. of teeth Z: 4

Shank: DIN 6535 HA to h6

Chamfer mill: 30 degrees

No. of teeth Z: 4

Dimension S: 7.9 mm

Overall length L: 63 mm

Shank Ø D<sub>s</sub>: 8 mm

Feed f<sub>z</sub> in steel < 900 N/mm<sup>2</sup>: 0.06 mm

**Technical description**

Overall length L	63 mm
Shank Ø D <sub>s</sub>	8 mm
Cutting edge Ø D <sub>c</sub>	8 mm
Chamfer mill	30 degrees
Feed f <sub>z</sub> in steel < 900 N/mm <sup>2</sup>	0.06 mm

Corner chamfer angle	60 degrees
No. of teeth Z	4
Dimension S	7.9 mm
Shank	DIN 6535 HA to h6
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal $\varnothing$	h6
Helix angle	35 degrees
Direction of infeed	horizontal and oblique
Countersink tip angle	60 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	green
Type of product	End mill