

Garant

Copy and face mills, indexed, with bore, Ø D / number of teeth Z: 63/6 mm



Order data

Order number	212018 63/6
GTIN	4062406576653
Item class	210

Description

Version:

The latest generation of copy and face milling cutters. Indexed round inserts ensure stable conditions and secure the insert against accidental twisting during use. The optimised form fit between the indexable insert and insert seat ensures exceptional process reliability.

Note:

$a_{p,max} = 6.0 \text{ mm.}$

Use GARANT torque screwdriver TQ No. **211750 size 3.8** with bit No. **674252 size 15IP**.

Tool exchange: PowerCard

Through-coolant: yes

Number of cutting edges Z: 6

Ø D₃: 51 mm

Overall length L_{tot}: 40 mm

Mounting bore Ø: 22 mm

Circular interpolation milling Ø D_{min}: 102.4 mm

Circular interpolation milling Ø D_{max}: 125.2 mm

Technical description

Mounting bore Ø	22 mm
-----------------	-------

Cutting edge $\varnothing D_c$	63 mm
Circular interpolation milling $\varnothing D_{max}$	125.2 mm
$\varnothing D_3$	51 mm
suitable indexable insert	RPK.1204M0T
Through-coolant	yes
Pack of insert screws	219878 3 (15IP; 3.8 Nm)
Overall length L_{tot}	40 mm
Number of cutting edges Z	6
Circular interpolation milling $\varnothing D_{min}$	102.4 mm
Ramping length L for α_{max}	63.9 mm
Ramping angle α_{max}	5.4 degrees
Shank type	with bore
Milling head suitable for insert shape	round
Milling application	Circular milling
Milling application	Circular milling
Spacing of the cutters	unequal spacing
Tool exchange	PowerCard

Accessories

Set of insert screws 10 pieces Type 3	219878 3
---------------------------------------	----------