Garant

Side / parting off milling cutter with thread Steel width ap= 1.5 mm, \varnothing D: 50/4 mm



Order data

Order number	218416 50/4
GTIN	4062406238599
Item class	21P

Description

Version:

High-performance parting-off milling cutter system with choice of either collar and **low-cost steel blade** or collar and **high-precision temperature-resistant HSS blade.**Specially for use in deep cavities.

Application:

For slitting and parting off milling. For high repetition accuracy in series production it is preferable to use the HSS blade.

Attention:

Please order the assembly key No. 279940 1 separately. See catalogue page 758.

Note:

Side and parting-off milling cutters available up to \varnothing D = 200 mm.

Through-coolant: no

Number of cutting edges Z: 4

maximum cutting depth $a_{e\,max}$: 12.75 mm

Ø D₁ h6: 12.5 mm

Overall length L_{tot} for a_p 1.5 mm: 31.4 mm Overall length L_{tot} for a_p 2.2 mm: 32 mm

Ø D₂: 25 mm

Technical description

maximum cutting depth a _{e max}	12.75 mm
Overall length L _{tot} for a _p 2.2 mm	32 mm
Mounting thread M	M12
Ø D ₁ h6	12.5 mm
Cutting edge \varnothing D_c	50 mm
Number of cutting edges Z	4
\emptyset D ₂	25 mm
Overall length L_{tot} for a_p 1.5 mm	31.4 mm
suitable indexable insert	XC 1119
Width a_p	1.5 mm
Shank type	with thread
Tool material	HSS
Through-coolant	no
Type of product	Side milling cutter