

Garant

Side / parting off milling cutter with thread Steel width $a_p = 2.2$ mm, $\varnothing D$: 63/4 mm

**Order data**

Order number	218418 63/4
GTIN	4062406239442
Item class	21P

Description**Version:**

High-performance parting-off milling cutter system with choice of either collar and **low-cost steel blade** or collar and **high-precision temperature-resistant HSS blade**.

Specially for use in deep cavities.

Application:

For slitting and parting off milling. For high repetition accuracy in series production it is preferable to use the HSS blade.

Attention:

Please order the assembly key No. 279940 1 separately. See catalogue page 758.

Note:

Side and parting-off milling cutters available up to $\varnothing D = 200$ mm.

Through-coolant: no

Number of cutting edges Z: 4

maximum cutting depth $a_{e\max}$: 15.75 mm

$\varnothing D_1$ h6: 17 mm

Overall length L_{tot} for a_p 1.5 mm: 33.4 mm

Overall length L_{tot} for a_p 2.2 mm: 40 mm

$\varnothing D_2$: 29 mm

Technical description

Number of cutting edges Z	4
Mounting thread M	M16
Overall length L_{tot} for a_p 2.2 mm	40 mm
Overall length L_{tot} for a_p 1.5 mm	33.4 mm
$\varnothing D_1$ h6	17 mm
suitable indexable insert	XC.. 1119
Cutting edge $\varnothing D_c$	63 mm
$\varnothing D_2$	29 mm
maximum cutting depth $a_{e \text{ max}}$	15.75 mm
Width a_p	2.2 mm
Shank type	with thread
Tool material	Steel
Through-coolant	no
Type of product	Side milling cutter