



Indexable milling cutter 90° MEV, Plain shank, Ø D / number of teeth Z: 20/2 mm



Order data

Order number	226400 20/2
GTIN	4960664914043
Item class	250

Description

Version:

High-performance milling cutter with newly developed triangular indexable insert for corner and slot milling and ramping with lower cutting forces and increased stability.

Through-coolant: yes

maximum cutting depth $a_{p\max}$: 6 mm

Overhang L_1 : 26 mm

Overall length L_{tot} : 110 mm

Shank Ø D_s h6: 16 mm

suitable indexable insert: TOMT060508

Insert screw: 229723 1 (10IP; 2.0 Nm)

Technical description

Insert screw	229723 1 (10IP; 2.0 Nm)
Overhang L_1	26 mm
Shank Ø D_s h6	16 mm
Cutting edge Ø D_c	20 mm
maximum cutting depth $a_{p\max}$	6 mm
Overall length L_{tot}	110 mm
suitable indexable insert	TOMT060508
Number of cutting edges Z	2

Shank type	Plain shank
Setting angle κ	90 degrees
Milling application	End milling
Milling application	Plunging
Milling application	Ramping
Through-coolant	yes
Type	W
Type of product	Indexable insert cutter

Accessories

Clamping screw Type 1	229723 1
-----------------------	----------