

**HOLEX Pro Drill indexable drill Combination shank, 4xD, Ø DC: 30 mm****Order data**

| | |
|--------------|---------------|
| Order number | 235010 30 |
| GTIN | 4062406253615 |
| Item class | 22L |

Description**Version:**

HOLEX Pro Drill indexable drills combine cost efficiency with technically fully developed capability.

For use up to 4xD in challenging drilling applications.

Bore tolerance: -0.05 / +0.3 mm

Application:

With indexable inserts No. 235030 – 235082.

Both SOMT inserts for the outer insert seats and also XOMT inserts for the inner insert seats are required.

Supplied with:

With insert screws (supplied without indexable inserts).

Recommendation:

When spot-drilling reduce the feed rate by 70 %.

Overhang L_A : 150 mm

Shank $\varnothing D_s$: 32 mm

Shank length L_s : 60 mm

ISO code indexable insert: SOMT110408 / XOMT110406

Pack of insert screws: 232980 5 (TX15;3Nm)

Technical description

| | |
|--|------------------------------------|
| Shank $\varnothing D_s$ | 32 mm |
| Shank length L_s | 60 mm |
| Nominal $\varnothing D$ | 30 |
| Reach L_1 | 123 mm |
| Pack of insert screws | 232980 5 (TX15;3Nm) |
| ISO code indexable insert | SOMT110408 / XOMT110406 |
| Series | HOLEX Pro Drill |
| Number of cutting edges Z | 1 |
| Overall length L | 210 mm |
| Maximum adjustment limit V_{max} | 0.35 mm |
| Overhang L_A | 150 mm |
| Drill depth for indexable insert drill up to | 4×D |
| Shank | ISO 9766 |
| Use for drilling | limited drilling with oblique exit |
| Use for drilling | limited cross-drilling |
| Use for drilling | limited oblique spot drilling |
| Use for drilling | limited drilling through a stack |
| Use for drilling | limited drilling with oblique exit |
| Use for drilling | limited convexity |
| Through-coolant | yes |
| Machining strategy | HPC |

Accessories

| | |
|--|-------------|
| 6 mm blade for Torx® Torx® profile TX15 | 659922 TX15 |
| Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm | 659906 500 |