


**KOMET KUB Quatron® indexable drill ABS® shank, 3×D, Ø DC: 62 mm**

**Order data**

|              |               |
|--------------|---------------|
| Order number | 235505 62     |
| GTIN         | 4047109084759 |
| Item class   | 24P           |

**Description**
**Version:**

**With ABS® shank.**

**Application:**

With indexable inserts No. 236520 – 236576.

**Supplied with:**

Clamp screws (without indexable inserts).

**Note:**

For use only under **stable** machining conditions.

**Offset-axis drilling is possible up to  $V_{max} = 0.25$  mm**, e.g. with eccentric adjusting unit No. 239010 – 239012.

Maximum  $\varnothing = D + 0.5$  mm achievable by offsetting.

Further sizes available on request.

for inch  $\varnothing$ : 2 7/16 inch

Overhang  $L_A$ : 241 mm

ABS® shank  $\varnothing D_s$ : 80 mm

ISO code indexable insert: SOEX 090408 32-..

Pack of insert screws: 239652 15IP1 (2.8 Nm)

**Technical description**

|                              |                       |
|------------------------------|-----------------------|
| Reach $L_1$                  | 186 mm                |
| Number of cutting edges Z    | 1                     |
| ABS® shank $\varnothing D_s$ | 80 mm                 |
| Pack of insert screws        | 239652 15IP1 (2.8 Nm) |

|                                              |                        |
|----------------------------------------------|------------------------|
| ISO code indexable insert                    | SOEX 090408 32-..      |
| Series                                       | KUB Quatron®           |
| Nominal Ø D                                  | 62                     |
| for inch Ø                                   | 2 7/16 inch            |
| Overhang L <sub>A</sub>                      | 241 mm                 |
| Drill depth for indexable insert drill up to | 3×D                    |
| Shank                                        | ABS                    |
| Use for drilling                             | Centre drilling        |
| Use for drilling                             | limited cross-drilling |
| Use for drilling                             | Cross-drilling         |
| Use for drilling                             | Centre drilling        |
| Use for drilling                             | Aperture               |
| Use for drilling                             | oblique exit           |
| Use for drilling                             | convex                 |
| Use for drilling                             | oblique spot drilling  |
| Through-coolant                              | yes                    |

## Accessories

|                                                                  |              |
|------------------------------------------------------------------|--------------|
| Torx Plus® insert screw set 10 pieces Drive 15IP1                | 239652 15IP1 |
| PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 15IP | 674252 15IP  |
| Torque screwdriver, fixed setting set torque 2,8 Nm              | 211750 2,8   |