

## Garant

### Solid carbide reaming head HPC H7 steel Blind hole, TiAlN, Nominal Ø D: 16 mm



#### Order data

Order number	239725 16
GTIN	4045197575869
Item class	23A

#### Description

##### Version:

Interchangeable head reamer system **finish ground for fit IT7**. Cutter geometry matched to the application.

**System concentricity  $\leq 5 \mu\text{m}$  (depending on the head and holder) when mounted.**

With short, straight flutes.

##### Application:

**For blind holes.**

For HPC/HSC reaming.

##### Note:

**Total usable length** =  $L_1$  (arbor No. 239740 / 239745) +  $l$  (interchangeable head No. 239710 to 239735).

Clamping wrench = No. 219987.

Insert for torque wrench = No. 219986.

Further sizes available on request.

Arbor size: 10 mm

Cutter length  $l_1$ : 12 mm

Head length  $l$ : 22 mm

Number of cutting edges  $Z$ : 6

Feed  $f$  in steel  $< 1100 \text{ N/mm}^2$ : 0.8 mm/rev.

#### Technical description

Head length $l$	22 mm
-----------------	-------

Arbor size	10 mm
Nominal Ø D	16 mm
Number of cutting edges Z	6
Feed f in steel < 1100 N/mm <sup>2</sup>	0.8 mm/rev.
Cutter length l <sub>1</sub>	12 mm
Width across flats	8 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Hole tolerance	H7
Application for type of drilling	for blind holes and through holes
Machining strategy	HPC
Through-coolant	yes
Semi-Standard	yes
suitable arbor	GARANT TopCut
Type of product	Cutter insert for reaming