

Garant

**Solid carbide reaming head HPC H7 stainless steel Through hole, TiAlN,
Nominal Ø D: 20 mm**



Order data

Order number	239730 20
GTIN	4045197576071
Item class	23A

Description

Version:

Interchangeable head reamer system **finish ground for fit IT7**. Cutter geometry matched to the application.

System concentricity $\leq 5 \mu\text{m}$ (depending on the head and holder) when mounted.

With short flutes and left-hand helix.

Application:

For through holes.

For HPC/HSC reaming.

Note:

Total usable length = L_1 (arbor No. 239740 / 239745) + l (interchangeable head No. 239710 to 239735).

Clamping wrench = No. 219987.

Insert for torque wrench = No. 219986.

Further sizes available on request.

Arbor size: 16 mm

Cutter length l_1 : 14 mm

Head length l : 26 mm

Number of cutting edges Z : 8

Feed f in stainless steel $< 900 \text{ N/mm}^2$: 0.4 mm/rev.

Technical description

Cutter length l_1	14 mm
---------------------	-------

Head length l	26 mm
Feed f in stainless steel < 900 N/mm ²	0.4 mm/rev.
Arbor size	16 mm
Number of cutting edges Z	8
Nominal Ø D	20 mm
Width across flats	13 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Hole tolerance	H7
Application for type of drilling	for through holes
Machining strategy	HPC
Through-coolant	yes
Semi-Standard	yes
suitable arbor	GARANT TopCut
Type of product	Cutter insert for reaming