

## Garant

**Solid carbide reaming head HPC H7 stainless steel Blind hole, TiAlN, Nominal Ø D: 23 mm**



### Order data

Order number	239735 23
GTIN	4045197707659
Item class	23A

### Description

#### Version:

Interchangeable head reamer system **finish ground for fit IT7**. Cutter geometry matched to the application.

**System concentricity  $\leq 5 \mu\text{m}$  (depending on the head and holder) when mounted.**

With short, straight flutes.

#### Application:

**For blind holes.**

For HPC/HSC reaming.

#### Note:

**Total usable length** =  $L_1$  (arbor No. 239740 / 239745) +  $l$  (interchangeable head No. 239710 to 239735).

Clamping wrench = No. 219987.

Insert for torque wrench = No. 219986.

Further sizes available on request.

Arbor size: 16 mm

Cutter length  $l_1$ : 14 mm

Head length  $l$ : 26 mm

Number of cutting edges  $Z$ : 8

Feed  $f$  in stainless steel  $< 900 \text{ N/mm}^2$ : 0.5 mm/rev.

### Technical description

Cutter length $l_1$	14 mm
---------------------	-------

Arbor size	16 mm
Feed f in stainless steel < 900 N/mm <sup>2</sup>	0.5 mm/rev.
Head length l	26 mm
Number of cutting edges Z	8
Nominal Ø D	23 mm
Width across flats	13 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Hole tolerance	H7
Application for type of drilling	for blind holes
Machining strategy	HPC
Through-coolant	yes
Semi-Standard	yes
suitable arbor	GARANT TopCut
Type of product	Cutter insert for reaming