

**Garant**
**Arbor 90°, cylindrical with IC long, Type: 29**

**Order data**

Order number	239745 29
GTIN	4062406115784
Item class	23A

**Description**
**Version:**

Version suitable for NC with straight shank  $\varnothing$  for standard arbors especially in **hydraulic chucks** or **high precision collet chucks** for very high accuracy and process reliability.

**Note:**

Observe the mounting size of the holder and reaming heads. For further arbors see No. 210550 – 210582 and No. 212000.

Shank: DIN 6535 HA to h6

suitable for through hole  $\varnothing$ : 32.21 - 50 mm

suitable for blind hole  $\varnothing$ : 40.21 - 50 mm

Overall length  $L_{tot}$ : 216 mm

Reach  $L_1$ : 152.5 mm

Shank  $\varnothing D_s$  h6: 32 mm

recommended tightening torque: 35 Nm

**Technical description**

recommended tightening torque	35 Nm
Overall length $L_{tot}$	216 mm
Shank $\varnothing D_s$ h6	32 mm
Reach $L_1$	152.5 mm
suitable for blind hole $\varnothing$	40.21 - 50 mm
suitable for through hole $\varnothing$	32.21 - 50 mm
Series	TopCut
Through-coolant	yes

Shank	DIN 6535 HA to h6
Type of product	Threaded copy mill arbor