KOMET '

KOMET REAMAX[®] TS reaming head H7 Cermet ASG3000, DST, Nominal Ø D: 32 mm



Order data

Order number	239811 32
GTIN	4047109236639
Item class	27E

Description

Version:

Reaming heads finish ground for fit H7.

Cutter geometry matched to the application. Adjustable down to the μ m range for wear compensation and for very tight basic tolerances down to IT4. For use in through holes up to 5×D.

In geometry **ASG3000** with lead angle 45° and additional chip flute for positive chip clearance along the cutting edge. For **blind and through holes.**

Note:

· Other sizes available on request on short lead times.

· See No. 239880 – 239940 for suitable holders.

• Application data apply to through holes.

Through-coolant: yes for holders No. 239880 – 239940: 27 – 34.99 Cutter length l₁: 6 mm Head length l: 25 mm Number of cutting edges Z: 8 Feed f in steel < 750 N/mm²: 1.2 mm/rev.

Technical description

Number of cutting edges Z

8

Feed f in steel < 750 N/mm ²	1.2 mm/rev.
Head length l	25 mm
Nominal Ø D	32 mm
Cutter length l ₁	6 mm
for holders No. 239880 – 239940	27 – 34.99
Coating	DST
Hole tolerance	H7
Application for type of drilling	for blind holes and through holes
Through-coolant	yes
Type of product	Cutter insert for reaming