



KOMET Reamax® TS holder DAH® Zero Plain shank, short, for reaming head Ø D: 18-19,99 mm



Order data

Order number	239930 18-19,99
GTIN	4047109229372
Item class	27E

Description

Version:

The holder is pre-loaded and set to < 0.005 mm run-out. For run-out accuracies to precision < 3 µm, longer tool life, and higher process reliability.

Suitable for :

Reaming heads No. 239805; 239811; 239816; 239822; 239826.

Supplied with:

Holder complete with pull stud, spanner for pull stud and activation key.

Please order a hexagon key L-wrench separately if required.

Through-coolant: yes

Overhang A: 80 mm

Overall length L_{tot} : 145 mm

Shank length L_s : 50 mm

Shank Ø D_s h6: 20 mm

Pull stud No. 239900: 1

Wrench No. 239901: 5AF

Technical description

Shank length L_s	50 mm
Activation wrench No. 239902	8IP(1.5Nm)
Overall length L_{tot}	145 mm
Pull stud No. 239900	1
Wrench No. 239901	5AF
for reaming head Ø D	18 - 19.99 mm

Overhang A	80 mm
Shank $\varnothing D_s$ h6	20 mm
Shank type	short
Through-coolant	yes
Type of product	Reaming tool for detachable cutters

Accessories

Pull stud Type 1	239900 1
Wrench for pull studs Drive SW5	239901 SW5