



## KOMET Reamax® TS holder DAH® Zero Plain shank, short, for reaming head Ø D: 20-21,99 mm



### Order data

Order number	239930 20-21,99
GTIN	4047109229389
Item class	27E

### Description

#### Version:

The holder is pre-loaded and set to < 0.005 mm run-out. For run-out accuracies to precision < 3 µm, longer tool life, and higher process reliability.

#### Suitable for :

Reaming heads No. 239805; 239811; 239816; 239822; 239826.

#### Supplied with:

Holder complete with pull stud, spanner for pull stud and activation key.

Please order a hexagon key L-wrench separately if required.

Through-coolant: yes

Overhang A: 80 mm

Overall length  $L_{tot}$ : 145 mm

Shank length  $L_s$ : 50 mm

Shank Ø  $D_s$  h6: 20 mm

Pull stud No. 239900: 2

Wrench No. 239901: 5AF

### Technical description

Overall length $L_{tot}$	145 mm
Wrench No. 239901	5AF
Shank length $L_s$	50 mm
Overhang A	80 mm
Pull stud No. 239900	2
Activation wrench No. 239902	2.5AF (2.5Nm)

for reaming head $\varnothing$ D	20 - 21.99 mm
Shank $\varnothing$ D <sub>s</sub> h6	20 mm
Shank type	short
Through-coolant	yes
Type of product	Reaming tool for detachable cutters

---

## Accessories

Pull stud Type 2	239900 2
Wrench for pull studs Drive SW5	239901 SW5