



KOMET Reamax® TS holder DAH® Zero Plain shank, long, for reaming head Ø D: 27-34,99 mm



Order data

Order number	239940 27-34,99
GTIN	4047109280083
Item class	27E

Description

Version:

The holder is pre-loaded and set to < 0.005 mm run-out. For run-out accuracies to precision < 3 µm, longer tool life, and higher process reliability.

Suitable for :

Reaming heads No. 239805; 239811; 239816; 239822; 239826.

Supplied with:

Holder complete with pull stud, spanner for pull stud and activation key.

Please order a hexagon key L-wrench separately if required.

Through-coolant: yes

Overhang A: 180 mm

Overall length L_{tot} : 236 mm

Shank length L_s : 56 mm

Shank Ø D_s h6: 25 mm

Pull stud No. 239900: 4

Wrench No. 239901: 8AF

Technical description

Shank length L_s	56 mm
Overall length L_{tot}	236 mm
Wrench No. 239901	8AF
Pull stud No. 239900	4
for reaming head Ø D	27 - 34.99 mm
Overhang A	180 mm

Activation wrench No. 239902	3AF (5Nm)
Shank $\varnothing D_s$ h6	25 mm
Shank type	long
Through-coolant	yes
Type of product	Reaming tool for detachable cutters

Accessories

Pull stud Type 4	239900 4
Wrench for pull studs Drive SW8	239901 SW8