

**Garant**
**Boring bar, steel, right-hand, Shank  $\varnothing$  / insert size: 32/12 mm**

**Order data**

Order number	250034 32/12
GTIN	4062406082956
Item class	21U

**Description**

Boring bar, steel 32/12 mm Shank  $\varnothing$  D<sub>3</sub>: 35 mm  
 ISO code toolholder: A32X DCLNR/L12  
 Setting angle  $\kappa$ : 95 degrees  
 suitable indexable insert: CN.. 1204..  
 Minimum pre-drill  $\varnothing$  D<sub>min</sub>: 38 mm  
 Centre offset L<sub>3</sub>: 22 mm

**Technical description**

ISO code toolholder	A32X DCLNR/L12
Overall length L	288 mm
Minimum pre-drill $\varnothing$ D <sub>min</sub>	38 mm
Centre offset L <sub>3</sub>	22 mm
Shim screw	259027 2
Setting angle $\kappa$	95 degrees
suitable indexable insert	CN.. 1204..
Insert size	12 mm
Overhang L <sub>1</sub>	150 mm
Shim	259033 2
Clamping height L <sub>2</sub>	31 mm
Clamp, screw, O-ring	259035 4

Shank $\varnothing D_s$	35 mm
Application type	right-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar