


Garant
Boring bar steel, right-hand, Shank Ø / insert size: 1012/06 mm

Order data

Order number	260032 1012/06
GTIN	4045197979018
Item class	21T

Description

Boring bar steel 1012/06 mm Shank Ø D_s: 12 mm

ISO code toolholder: A1012K SCLCR/L06

Setting angle κ: 95 degrees

suitable indexable insert: CC.. 0602..

Minimum pre-drill Ø D_{min}: 13 mm

Centre offset L₃: 6.9 mm

Technical description

Clamping height L ₂	11 mm
Overall length L	125 mm
Pack of insert screws	269028 5
suitable indexable insert	CC.. 0602..
Head length L ₁	32.5 mm
Neck width	10 mm
ISO code toolholder	A1012K SCLCR/L06
Minimum pre-drill Ø D _{min}	13 mm
Insert size	6 mm
Centre offset L ₃	6.9 mm
Setting angle κ	95 degrees
Shank Ø D _s	12 mm

Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Boring bar set, steel, with IC Type SET06	260036 SET06