

**Garant**
**Boring bar steel, left-hand, Shank Ø / insert size: 0810/06 mm**

**Order data**

|              |                |
|--------------|----------------|
| Order number | 260033 0810/06 |
| GTIN         | 4045197979049  |
| Item class   | 21T            |

**Description**

Boring bar steel 0810/06 mm Shank Ø D<sub>s</sub>: 10 mm

ISO code toolholder: A0810J SCLCR/L06

Setting angle κ: 95 degrees

suitable indexable insert: CC.. 0602..

Minimum pre-drill Ø D<sub>min</sub>: 11 mm

Centre offset L<sub>3</sub>: 6 mm

**Technical description**

|                                      |                  |
|--------------------------------------|------------------|
| Centre offset L <sub>3</sub>         | 6 mm             |
| suitable indexable insert            | CC.. 0602..      |
| Minimum pre-drill Ø D <sub>min</sub> | 11 mm            |
| Clamping height L <sub>2</sub>       | 9 mm             |
| Pack of insert screws                | 269028 5         |
| Insert size                          | 6 mm             |
| ISO code toolholder                  | A0810J SCLCR/L06 |
| Head length L <sub>1</sub>           | 27 mm            |
| Neck width                           | 8 mm             |
| Setting angle κ                      | 95 degrees       |
| Overall length L                     | 110 mm           |
| Shank Ø D <sub>s</sub>               | 10 mm            |

|                    |            |
|--------------------|------------|
| Application type   | left-hand  |
| Boring depth up to | 3×D        |
| Standard           | DIN 8024   |
| Through-coolant    | yes        |
| Type of product    | Boring bar |

---

## Accessories

|                                                                                      |              |
|--------------------------------------------------------------------------------------|--------------|
| PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8                                | 674248 TX8   |
| Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm | 659906 500   |
| Boring bar set, steel, with IC Type SET06                                            | 260037 SET06 |