

Garant
Boring bar steel, left-hand, Shank Ø / insert size: 1216/06 mm

Order data

Order number	260033 1216/06
GTIN	4045197979063
Item class	21T

Description

Boring bar steel 1216/06 mm Shank Ø D_s: 16 mm

ISO code toolholder: A1216M SCLCR/L06

Setting angle κ: 95 degrees

suitable indexable insert: CC.. 0602..

Minimum pre-drill Ø D_{min}: 16 mm

Centre offset L₃: 8.9 mm

Technical description

Head length L ₁	42 mm
Pack of insert screws	269028 5
Minimum pre-drill Ø D _{min}	16 mm
Neck width	12 mm
suitable indexable insert	CC.. 0602..
ISO code toolholder	A1216M SCLCR/L06
Insert size	6 mm
Setting angle κ	95 degrees
Centre offset L ₃	8.9 mm
Clamping height L ₂	15 mm
Overall length L	150 mm
Shank Ø D _s	16 mm

Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Boring bar set, steel, with IC Type SET06	260037 SET06