

Garant
Boring bar carbide, right-hand, Shank \varnothing / insert size: 0408/04 mm

Order data

Order number	260318 0408/04
GTIN	4062406066307
Item class	21T

Description

Boring bar carbide 0408/04 mm Shank \varnothing D_s: 8 mm
 ISO code toolholder: E0408F SDUCR/L04
 Cutting point / joint: 8 mm
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 04T0..
 Minimum pre-drill \varnothing D_{min}: 5.6 mm

Technical description

Minimum pre-drill \varnothing D _{min}	5.6 mm
suitable indexable insert	DC.. 04T0..
Overall length L	80 mm
Centre offset L ₃	3 mm
Clamping height L ₂	7.5 mm
Insert size	4 mm
ISO code toolholder	E0408F SDUCR/L04
Pack of insert screws	269028 26
Neck width	4 mm
Head length L ₁	26 mm
Setting angle κ	93 degrees
Cutting point / joint	8 mm

Shank $\varnothing D_s$	8 mm
Application type	right-hand
Boring depth up to	8xD
Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX5	674248 TX5