

Garant
Boring bar carbide, left-hand, Shank \varnothing / insert size: 0408/04 mm

Order data

Order number	260321 0408/04
GTIN	4062406066734
Item class	21T

Description

Boring bar carbide 0408/04 mm Shank \varnothing D_s: 8 mm

ISO code toolholder: E0408F SDQCR/L04

Setting angle κ : 107.5 degrees

suitable indexable insert: DC.. 04T0..

Minimum pre-drill \varnothing D_{min}: 5.6 mm

Centre offset L₃: 3 mm

Technical description

suitable indexable insert	DC.. 04T0..
Minimum pre-drill \varnothing D _{min}	5.6 mm
Pack of insert screws	269028 26
Clamping height L ₂	7.5 mm
Overall length L	80 mm
Head length L ₁	26 mm
Neck width	4 mm
ISO code toolholder	E0408F SDQCR/L04
Setting angle κ	107.5 degrees
Insert size	4 mm
Centre offset L ₃	3 mm
Shank \varnothing D _s	8 mm

Application type	left-hand
Boring depth up to	8×D
Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX5	674248 TX5
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500