

**Garant**
**Boring bar HSS, right-hand, Shank  $\varnothing$  / insert size: 8/07 mm**

**Order data**

Order number	260332 8/07
GTIN	4062406401085
Item class	21T

**Description**

Boring bar HSS 8/07 mm Shank  $\varnothing$   $D_s$ : 8 mm  
 ISO code toolholder: AH08K SDUCR/L07  
 Setting angle  $\kappa$ : 93 degrees  
 suitable indexable insert: DC.. 0702..  
 Minimum pre-drill  $\varnothing$   $D_{min}$ : 13.5 mm  
 Centre offset  $L_3$ : 7.5 mm

**Technical description**

Overall length L	125 mm
Pack of insert screws	269028 7
Setting angle $\kappa$	93 degrees
Clamping height $L_2$	7 mm
ISO code toolholder	AH08K SDUCR/L07
Minimum pre-drill $\varnothing$ $D_{min}$	13.5 mm
Insert size	7 mm
suitable indexable insert	DC.. 0702..
Centre offset $L_3$	7.5 mm
Shank $\varnothing$ $D_s$	8 mm
Application type	right-hand
Boring depth up to	5xD

Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Set of insert screws Type 7	269028 7
Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500