

**Garant**
**Boring bar HSS, left-hand, Shank  $\varnothing$  / insert size: 8/07 mm**

**Order data**

Order number	260333 8/07
GTIN	4062406401092
Item class	21T

**Description**

Boring bar HSS 8/07 mm Shank  $\varnothing$  D<sub>s</sub>: 8 mm

ISO code toolholder: AH08K SDUCR/L07

Setting angle  $\kappa$ : 93 degrees

suitable indexable insert: DC.. 0702..

Minimum pre-drill  $\varnothing$  D<sub>min</sub>: 13.5 mm

Centre offset L<sub>3</sub>: 7.5 mm

**Technical description**

Overall length L	125 mm
Clamping height L <sub>2</sub>	7 mm
Centre offset L <sub>3</sub>	7.5 mm
Minimum pre-drill $\varnothing$ D <sub>min</sub>	13.5 mm
Pack of insert screws	269028 7
suitable indexable insert	DC.. 0702..
ISO code toolholder	AH08K SDUCR/L07
Insert size	7 mm
Setting angle $\kappa$	93 degrees
Shank $\varnothing$ D <sub>s</sub>	8 mm
Application type	left-hand
Boring depth up to	5×D

Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7