

## Garant

### Boring bar, steel, right-hand, Shank $\varnothing$ / insert size: 1012/07 mm



#### Order data

Order number	260340 1012/07
GTIN	4062406099114
Item class	21T

#### Description

Boring bar, steel 1012/07 mm Shank  $\varnothing$  D<sub>s</sub>: 12 mm

ISO code toolholder: A1012K SDQCR/L07

Setting angle  $\kappa$ : 107.5 degrees

suitable indexable insert: DC.. 0702..

Minimum pre-drill  $\varnothing$  D<sub>min</sub>: 15.5 mm

Centre offset L<sub>3</sub>: 9 mm

#### Technical description

ISO code toolholder	A1012K SDQCR/L07
Minimum pre-drill $\varnothing$ D <sub>min</sub>	15.5 mm
Head length L <sub>1</sub>	27.5 mm
Neck width	10.7 mm
Centre offset L <sub>3</sub>	9 mm
Clamping height L <sub>2</sub>	11 mm
Pack of insert screws	269028 7
suitable indexable insert	DC.. 0702..
Setting angle $\kappa$	107.5 degrees
Insert size	7 mm
Overall length L	125 mm
Usable depth T	4 mm

Shank $\varnothing D_s$	12 mm
Application type	right-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8