

Garant

Boring bar, steel, right-hand, Shank \varnothing / insert size: 1216/07 mm



Order data

Order number	260340 1216/07
GTIN	4062406099121
Item class	21T

Description

Boring bar, steel 1216/07 mm Shank \varnothing D_s: 16 mm

ISO code toolholder: A1216M SDQCR/L07

Setting angle κ : 107.5 degrees

suitable indexable insert: DC.. 0702..

Minimum pre-drill \varnothing D_{min}: 19.5 mm

Centre offset L₃: 11 mm

Technical description

Head length L ₁	39.5 mm
ISO code toolholder	A1216M SDQCR/L07
Setting angle κ	107.5 degrees
Minimum pre-drill \varnothing D _{min}	19.5 mm
Centre offset L ₃	11 mm
Neck width	12 mm
Pack of insert screws	269028 7
Overall length L	150 mm
Insert size	7 mm
suitable indexable insert	DC.. 0702..
Clamping height L ₂	15 mm
Usable depth T	5 mm

Shank $\varnothing D_s$	16 mm
Application type	right-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8