

## Garant

### Boring bar, steel, left-hand, Shank $\varnothing$ / insert size: 0408/04 mm



#### Order data

Order number	260341 0408/04
GTIN	4062406066796
Item class	21T

#### Description

Boring bar, steel 0408/04 mm Shank  $\varnothing$  D<sub>s</sub>: 8 mm  
 ISO code toolholder: A0408F SDQCR/L04  
 Setting angle  $\kappa$ : 107.5 degrees  
 suitable indexable insert: DC.. 04T0..  
 Minimum pre-drill  $\varnothing$  D<sub>min</sub>: 5.2 mm  
 Centre offset L<sub>3</sub>: 2.6 mm

#### Technical description

Clamping height L <sub>2</sub>	7.5 mm
Pack of insert screws	269028 26
Overall length L	80 mm
Minimum pre-drill $\varnothing$ D <sub>min</sub>	5.2 mm
Setting angle $\kappa$	107.5 degrees
Neck width	4 mm
Insert size	4 mm
ISO code toolholder	A0408F SDQCR/L04
Head length L <sub>1</sub>	15 mm
suitable indexable insert	DC.. 04T0..
Centre offset L <sub>3</sub>	2.6 mm
Usable depth T	1.1 mm

Shank $\varnothing D_s$	8 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX5	674248 TX5
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500