

Garant

Boring bar, steel, left-hand, Shank \varnothing / insert size: 0810/07 mm



Order data

Order number	260341 0810/07
GTIN	4062406099138
Item class	21T

Description

Boring bar, steel 0810/07 mm Shank \varnothing D_s: 10 mm
 ISO code toolholder: A0810H SDQCR/L07
 Setting angle κ : 107.5 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill \varnothing D_{min}: 12.5 mm
 Centre offset L₃: 6.4 mm

Technical description

Clamping height L ₂	9 mm
Overall length L	100 mm
Head length L ₁	22.4 mm
Pack of insert screws	269028 7
Neck width	8.4 mm
suitable indexable insert	DC.. 0702..
ISO code toolholder	A0810H SDQCR/L07
Setting angle κ	107.5 degrees
Centre offset L ₃	6.4 mm
Minimum pre-drill \varnothing D _{min}	12.5 mm
Insert size	7 mm
Usable depth T	3 mm

Shank $\varnothing D_s$	10 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8