

**Garant**
**Boring bar, steel, left-hand, Shank  $\varnothing$  / insert size: 1012/07 mm**

**Order data**

Order number	260341 1012/07
GTIN	4062406099145
Item class	21T

**Description**

Boring bar, steel 1012/07 mm Shank  $\varnothing$  D<sub>s</sub>: 12 mm  
 ISO code toolholder: A1012K SDQCR/L07  
 Setting angle  $\kappa$ : 107.5 degrees  
 suitable indexable insert: DC.. 0702..  
 Minimum pre-drill  $\varnothing$  D<sub>min</sub>: 15.5 mm  
 Centre offset L<sub>3</sub>: 9 mm

**Technical description**

Overall length L	125 mm
Setting angle $\kappa$	107.5 degrees
Insert size	7 mm
Pack of insert screws	269028 7
Centre offset L <sub>3</sub>	9 mm
Clamping height L <sub>2</sub>	11 mm
ISO code toolholder	A1012K SDQCR/L07
suitable indexable insert	DC.. 0702..
Neck width	10.7 mm
Minimum pre-drill $\varnothing$ D <sub>min</sub>	15.5 mm
Head length L <sub>1</sub>	27.5 mm
Usable depth T	4 mm

Shank $\varnothing D_s$	12 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500