

## Garant

### Boring bar, steel, left-hand, Shank Ø / insert size: 1216/07 mm



#### Order data

Order number	260341 1216/07
GTIN	4062406099152
Item class	21T

#### Description

Boring bar, steel 1216/07 mm Shank Ø D<sub>s</sub>: 16 mm  
 ISO code toolholder: A1216M SDQCR/L07  
 Setting angle κ: 107.5 degrees  
 suitable indexable insert: DC.. 0702..  
 Minimum pre-drill Ø D<sub>min</sub>: 19.5 mm  
 Centre offset L<sub>3</sub>: 11 mm

#### Technical description

Pack of insert screws	269028 7
Insert size	7 mm
Overall length L	150 mm
Centre offset L <sub>3</sub>	11 mm
ISO code toolholder	A1216M SDQCR/L07
Neck width	12 mm
suitable indexable insert	DC.. 0702..
Minimum pre-drill Ø D <sub>min</sub>	19.5 mm
Clamping height L <sub>2</sub>	15 mm
Head length L <sub>1</sub>	39.5 mm
Setting angle κ	107.5 degrees
Usable depth T	5 mm

Shank $\varnothing D_s$	16 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8