

Garant
Boring bar steel, right-hand, Shank Ø / insert size: 0408/04 mm

Order data

Order number	260342 0408/04
GTIN	4062406066802
Item class	21T

Description

Boring bar steel 0408/04 mm Shank Ø D_s : 8 mm
 ISO code toolholder: A0408F SDUCR/L04
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 04T0..
 Minimum pre-drill Ø D_{min} : 5.2 mm
 Centre offset L_3 : 3 mm

Technical description

Minimum pre-drill Ø D_{min}	5.2 mm
Neck width	4 mm
Centre offset L_3	3 mm
suitable indexable insert	DC.. 04T0..
Clamping height L_2	7.5 mm
Overall length L	80 mm
ISO code toolholder	A0408F SDUCR/L04
Head length L_1	15 mm
Setting angle κ	93 degrees
Pack of insert screws	269028 26
Insert size	4 mm
Usable depth T	1.5 mm

Shank $\varnothing D_s$	8 mm
Application type	right-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX5	674248 TX5