

Garant

Boring bar steel, right-hand, Shank \varnothing / insert size: 1216/07 mm



Order data

Order number	260342 1216/07
GTIN	4045197979094
Item class	21T

Description

Boring bar steel 1216/07 mm Shank \varnothing D_s : 16 mm
 ISO code toolholder: A1216M SDUCR/L07
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill \varnothing D_{min} : 18 mm
 Centre offset L_3 : 11 mm

Technical description

Neck width	12 mm
ISO code toolholder	A1216M SDUCR/L07
Insert size	7 mm
Minimum pre-drill \varnothing D_{min}	18 mm
Setting angle κ	93 degrees
Clamping height L_2	15 mm
Pack of insert screws	269028 7
Centre offset L_3	11 mm
Overall length L	150 mm
suitable indexable insert	DC.. 0702..
Head length L_1	40.5 mm
Usable depth T	4.9 mm

Shank $\varnothing D_s$	16 mm
Application type	right-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Boring bar set, steel, with IC Type SET07	260346 SET07