

Garant
Boring bar steel, left-hand, Shank \varnothing / insert size: 0408/04 mm

Order data

Order number	260343 0408/04
GTIN	4062406066819
Item class	21T

Description

Boring bar steel 0408/04 mm Shank $\varnothing D_s$: 8 mm

ISO code toolholder: A0408F SDUCR/L04

Setting angle κ : 93 degrees

suitable indexable insert: DC.. 04T0..

Minimum pre-drill $\varnothing D_{min}$: 5.2 mm

Centre offset L_3 : 3 mm

Technical description

Overall length L	80 mm
Neck width	4 mm
ISO code toolholder	A0408F SDUCR/L04
suitable indexable insert	DC.. 04T0..
Pack of insert screws	269028 26
Head length L_1	15 mm
Centre offset L_3	3 mm
Setting angle κ	93 degrees
Insert size	4 mm
Clamping height L_2	7.5 mm
Minimum pre-drill $\varnothing D_{min}$	5.2 mm
Usable depth T	1.5 mm

Shank $\varnothing D_s$	8 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX5	674248 TX5
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500