

Garant
Boring bar steel, left-hand, Shank Ø / insert size: 0810/07 mm

Order data

Order number	260343 0810/07
GTIN	4045197979100
Item class	21T

Description

Boring bar steel 0810/07 mm Shank Ø D_s: 10 mm

ISO code toolholder: A0810H SDUCR/L07

Setting angle κ: 93 degrees

suitable indexable insert: DC.. 0702..

Minimum pre-drill Ø D_{min}: 12.5 mm

Centre offset L₃: 6.5 mm

Technical description

Head length L ₁	22.5 mm
Minimum pre-drill Ø D _{min}	12.5 mm
Pack of insert screws	269028 7
Insert size	7 mm
ISO code toolholder	A0810H SDUCR/L07
Neck width	7 mm
Clamping height L ₂	9 mm
Centre offset L ₃	6.5 mm
Overall length L	100 mm
suitable indexable insert	DC.. 0702..
Setting angle κ	93 degrees
Usable depth T	4.4 mm

Shank Ø D _s	10 mm
Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Boring bar set, steel, with IC Type SET07	260347 SET07