

Garant
Boring bar, steel, left-hand, Shank Ø / insert size: 08/04 mm

Order data

Order number	260345 08/04
GTIN	4062406066765
Item class	21T

Description

Boring bar, steel 08/04 mm Shank Ø D_s: 8 mm

ISO code toolholder: A08F SDXCR/L04

Setting angle κ: 93 degrees

suitable indexable insert: DC.. 04T0..

Minimum pre-drill Ø D_{min}: 9.2 mm

Centre offset L₃: 5 mm

Technical description

Overall length L	80 mm
Pack of insert screws	269028 26
Clamping height L ₂	7.5 mm
ISO code toolholder	A08F SDXCR/L04
suitable indexable insert	DC.. 04T0..
Minimum pre-drill Ø D _{min}	9.2 mm
Insert size	4 mm
Setting angle κ	93 degrees
Head length L ₁	15 mm
Centre offset L ₃	5 mm
Usable depth T	3 mm
Shank Ø D _s	8 mm

Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX5	674248 TX5
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500