

**Garant**
**Boring bar, steel, left-hand, Shank  $\varnothing$  / insert size: 10/04 mm**

**Order data**

Order number	260345 10/04
GTIN	4062406066772
Item class	21T

**Description**

Boring bar, steel 10/04 mm Shank  $\varnothing D_s$ : 10 mm  
 ISO code toolholder: A10H SDXCR/L04  
 Setting angle  $\kappa$ : 93 degrees  
 suitable indexable insert: DC.. 04T0..  
 Minimum pre-drill  $\varnothing D_{min}$ : 12.5 mm  
 Centre offset  $L_3$ : 7 mm

**Technical description**

Overall length L	100 mm
Minimum pre-drill $\varnothing D_{min}$	12.5 mm
Clamping height $L_2$	9 mm
Insert size	4 mm
Setting angle $\kappa$	93 degrees
suitable indexable insert	DC.. 04T0..
Head length $L_1$	22 mm
ISO code toolholder	A10H SDXCR/L04
Centre offset $L_3$	7 mm
Pack of insert screws	269028 26
Usable depth T	5 mm
Shank $\varnothing D_s$	10 mm

Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX5	674248 TX5
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500