



Boring bar set, steel, without IC, right-hand, Type: SET07



Order data

| | |
|--------------|---------------|
| Order number | 260348 SET07 |
| GTIN | 4062406074982 |
| Item class | 29W |

Description

Version:

Without through-coolant feed.

Supplied with:

Plastic case

Standard: DIN 8024

ISO code toolholder: S0810H SDUCR07; S1012K SDUCR07; S1216M SDUCR07

suitable indexable insert: DC..0702..

Minimum pre-drill $\varnothing D_{\min}$: 12 mm

Minimum pre-drill $\varnothing D_{\min}$: 15.5 mm

Minimum pre-drill $\varnothing D_{\min}$: 18 mm

Centre offset L_3 : 6.5 mm

Technical description

| | |
|---------------------------|--|
| suitable indexable insert | DC..0702.. |
| ISO code toolholder | S0810H SDUCR07; S1012K SDUCR07; S1216M SDUCR07 |
| Pack of insert screws | 269028 7 |

| | |
|--|------------|
| Minimum pre-drill $\varnothing D_{\min}$ | 12 mm |
| Minimum pre-drill $\varnothing D_{\min}$ | 15.5 mm |
| Minimum pre-drill $\varnothing D_{\min}$ | 18 mm |
| Clamping height L_2 | 9 mm |
| Clamping height L_2 | 11 mm |
| Clamping height L_2 | 15 mm |
| Centre offset L_3 | 6.5 mm |
| Centre offset L_3 | 9 mm |
| Centre offset L_3 | 11 mm |
| Head length L_1 | 22.5 mm |
| Head length L_1 | 27.5 mm |
| Head length L_1 | 40.5 mm |
| Overall length L | 100 mm |
| Overall length L | 125 mm |
| Overall length L | 150 mm |
| Neck width L_4 | 8 mm |
| Neck width L_4 | 10 mm |
| Neck width L_4 | 12 mm |
| Application type | right-hand |
| Boring depth up to | 3×D |
| Standard | DIN 8024 |
| Type of product | Boring bar |