

Garant

Boring bar carbide, left-hand, Shank \varnothing / insert size: 8/05 mm



Order data

| | |
|--------------|---------------|
| Order number | 261333 8/05 |
| GTIN | 4062406283582 |
| Item class | 21T |

Description

Boring bar carbide 8/05 mm Shank \varnothing D_s : 8 mm
 ISO code toolholder: E08F SVLCR/L05
 Setting angle κ : 95 degrees
 suitable indexable insert: VC.. 0501..
 Minimum pre-drill \varnothing D_{min} : 9.2 mm
 Centre offset L_3 : 5 mm

Technical description

| | |
|---|----------------|
| Insert size | 5 mm |
| Neck width | 6 mm |
| Overall length L | 80 mm |
| Overhang L_1 recessed holders | 26 mm |
| ISO code toolholder | E08F SVLCR/L05 |
| Pack of insert screws | 269435 2 |
| Setting angle κ | 95 degrees |
| Clamping height L_2 | 7.5 mm |
| Minimum pre-drill \varnothing D_{min} | 9.2 mm |
| Centre offset L_3 | 5 mm |
| suitable indexable insert | VC.. 0501.. |
| Usable depth T | 3 mm |

| | |
|-------------------------|------------|
| Shank $\varnothing D_s$ | 8 mm |
| Application type | left-hand |
| Boring depth up to | 8xD |
| Tool material | Carbide |
| Standard | DIN 8024 |
| Through-coolant | yes |
| Type of product | Boring bar |

Accessories

| | |
|---------------------------------------|----------|
| Set of insert screws 10 pieces Type 2 | 269435 2 |
|---------------------------------------|----------|