



Boring bar carbide, right-hand, Shank \varnothing / insert size: 8/05 mm



Order data

| | |
|--------------|---------------|
| Order number | 261336 8/05 |
| GTIN | 4062406285524 |
| Item class | 21T |

Description

Boring bar carbide 8/05 mm ISO code toolholder: E08F SVVCR/L05

Setting angle κ : 72.5 degrees

suitable indexable insert: VC.. 0501..

Minimum pre-drill $\varnothing D_{\min}$: 10.2 mm

Centre-line offset: 5 mm

Clamping height H: 7.5 mm

Technical description

| | |
|--|----------------|
| Free length | 26 mm |
| Overall length L | 80 mm |
| Minimum pre-drill $\varnothing D_{\min}$ | 10.2 mm |
| Overhang L_1 recessed holders | 26 mm |
| Shank \varnothing | 8 mm |
| Insert size | 5 mm |
| ISO code toolholder | E08F SVVCR/L05 |
| Clamping height H | 7.5 mm |
| Neck width | 6 mm |
| suitable indexable insert | VC.. 0501.. |
| Pack of insert screws | 269435 2 |
| Centre-line offset | 5 mm |

| | |
|------------------------|-------------------------------|
| Setting angle κ | 72.5 degrees |
| Application type | right-hand |
| Boring depth up to | 8xD |
| Tool material | Carbide |
| Standard | DIN 8024 |
| Through-coolant | yes |
| Shank type | Boring bar |
| Application | Internal longitudinal turning |
| Type of product | Boring bar |

Accessories

| | |
|---------------------------------------|----------|
| Set of insert screws 10 pieces Type 2 | 269435 2 |
|---------------------------------------|----------|