



Boring bar carbide, left-hand, Shank \varnothing / insert size: 12/07 mm



Order data

Order number	261337 12/07
GTIN	4062406285586
Item class	21T

Description

Boring bar carbide 12/07 mm ISO code toolholder: E12K SVVCR/L07

Setting angle κ : 72.5 degrees

suitable indexable insert: VC.. 0702..

Minimum pre-drill $\varnothing D_{\min}$: 15.5 mm

Centre-line offset: 9 mm

Clamping height H: 11 mm

Technical description

Free length	40 mm
Pack of insert screws	269435 3
Centre-line offset	9 mm
Insert size	7 mm
suitable indexable insert	VC.. 0702..
Neck width	9 mm
Overall length L	125 mm
Minimum pre-drill $\varnothing D_{\min}$	15.5 mm
Overhang L_1 recessed holders	40 mm
Shank \varnothing	12 mm
Clamping height H	11 mm
ISO code toolholder	E12K SVVCR/L07

Setting angle κ	72.5 degrees
Application type	left-hand
Boring depth up to	8xD
Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Shank type	Boring bar
Application	Internal longitudinal turning
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces Type 3	269435 3
---------------------------------------	----------