Garant

Boring bar carbide, right-hand, Shank ∅ / insert size: 16/07 mm

Order data

Order number	261342 16/07
GTIN	4062406285630
Item class	21T

Description

Boring bar carbide 16/07 mmISO code toolholder: E16M SV95CR/L07
Setting angle κ: 95 degrees
suitable indexable insert: VC.. 0702..
Minimum pre-drill ∅ D_{min}: 19.5 mm
Centre-line offset: 11 mm
Clamping height H: 15 mm

Technical description

Overall length L	150 mm
Centre-line offset	11 mm
Neck width	12.9 mm
ISO code toolholder	E16M SV95CR/L07
Free length	55 mm
Insert size	7 mm
Clamping height H	15 mm
Minimum pre-drill ∅ D_{min}	19.5 mm
Pack of insert screws	269435 3
Shank ∅	16 mm
Setting angle κ	95 degrees
suitable indexable insert	VC.. 0702..

Overhang L_1 recessed holders	55 mm
Application type	right-hand
Boring depth up to	8×D
Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Shank type	Boring bar
Application	Internal longitudinal turning
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces Type 3	269435 3