



Boring bar carbide, left-hand, Shank \varnothing / insert size: 10/07 mm



Order data

Order number	261343 10/07
GTIN	4062406285654
Item class	21T

Description

Boring bar carbide 10/07 mm ISO code toolholder: E10H SV95CR/L07

Setting angle κ : 95 degrees

suitable indexable insert: VC.. 0702..

Minimum pre-drill $\varnothing D_{\min}$: 12.5 mm

Centre-line offset: 7 mm

Clamping height H: 9 mm

Technical description

ISO code toolholder	E10H SV95CR/L07
Setting angle κ	95 degrees
Overhang L_1 recessed holders	32 mm
Pack of insert screws	269435 3
Insert size	7 mm
Neck width	6.8 mm
suitable indexable insert	VC.. 0702..
Shank \varnothing	10 mm
Minimum pre-drill $\varnothing D_{\min}$	12.5 mm
Overall length L	100 mm
Centre-line offset	7 mm
Free length	32 mm

Clamping height H	9 mm
Application type	left-hand
Boring depth up to	8×D
Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Shank type	Boring bar
Application	Internal longitudinal turning
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces Type 3	269435 3
---------------------------------------	----------